

Processing up to 6 tons [13,500 lbs] p/m



MODEL: FD-200ML-SLIM

Make food waste easy to process with our bio-dehydrator. Use it as a soil amendment, send it to a compost facility, or dispose of it responsibly.

Load your food waste into the machine where it is macerated and heated to a point where the moisture is extracted from the reactor drum. The machine then condenses the steam and discharges a clear water condensate (no total suspended solids!). The remaining dry output is 80-90% volume-reduced, inert, pathogen free, compostable product with a variety of uses.

200kg capacity of food waste per cycle.

This model is specifically designed for facilities and cruise ships that can only be accessed through standard doors with a width of 36 inches (915mm). For example, this SLIM model is installed on Seabourn Cruise Line vessels. Average cycle times are 13-18 hours depending on the moisture content. Single button operation.

CAPACITY: 200kg / 450lb (per cycle)

LENGTH: 1452mm / 57.18in

DEPTH: 892mm / 35.12in
[Radiator Fan Detached]

HEIGHT: 1579mm / 62.18in

CYCLE TIME: 13-18 hours

Note: figures may vary due to psychrometrics as air density (height above sea level), air temperature, humidity etc.

Note: Specifications of all models may be changed without prior notice

** ML designates "Manual Load" ** AL designates "Automatic Load"

** Approximate capacity daily and capacity per cycle is a range and not to be construed as an exact calculation as the bio reactor drums are a fixed volume, but density and moisture content of food waste varies.

** 1CFM = 1CFM * 35.3 / 1CMM = 35.3CFM

MODEL	FD-200ML-SLIM
Cycle Times/Full Load (capacity per cycle)**	1 Cycle / 13-18hrs 200kg / 450lbs
Possible Cycles Per Day**	1-1.5 Cycle
Approximate Capacity per day (full 24 hours) **	250kg / 560lbs
NOTE: CYCLE TIME WILL VARY FROM LOAD TO LOAD DEPENDING ON THE MOISTURE CONTENT OF THE FOOD WASTE	
Depth	992mm / 39.05in
Depth / Radiator Fan Detached	892mm / 35.12in
Length/Width	1452mm / 57.18in
Height	1579mm / 62.18in
Height W/Lift	NO LIFT
External Condenser Size (L x W x H)	X
Drum Volume	350Liters / 92.466gal
Net weight of unit	600kg / 1325lbs
CFM output radiator	1200.2CFM = 34CMM
Delta T	86F/30c
BTU/hr = 1.08 x CFM x ΔT	111475
Converted to kW	32.7

FD-200ML-SLIM

